



marantz



MODEL 50

MODEL 50 Pure Analog Stereo Integrated Amplifier

Striking a perfect balance between power and elegance, the Marantz MODEL 50 is the ideal integrated amplifier to reveal the warmth, spaciousness, detail, and richness of each recording.

- No digital audio circuitry simplifies use and reduces audible interference.
- 70 watts per channel and Current Feedback Class A/B amplification maximizes speaker capability.
- A full suite of inputs and outputs for your sources, subwoofer, and even an extra power amplifier.
- Unique HDAM SA-3 discrete amplifier circuitry outperforms ICs used in competing amplifiers.
- Hear details in your vinyl records like never before using the Marantz Musical Phono EQ gain stage.
- Iconic Marantz porthole display is used for setup and to easily see your volume level.
- Meticulously crafted and robustly built, MODEL 50 design and style matches the most musical sound.



The Most Musical Sound

MODEL 50

Technical Specifications



Features	
Channels	2
Current Feedback Topology	Yes
Phono EQ: Standard / Marantz Musical / Marantz Musical Premium	No / Yes / No
Digital in: USB-B / optical / coaxial / USB-A	No / No / No / No
HDAM version	SA2, SA3
Power Transformer: Toroidal / EI	Yes / No
High Grade Audio Components	Yes
Customized Components	Yes
Symmetric PCB Layout	Yes
Aluminium extrusion heat sink	Yes
Balance / Bass / Treble / Loudness	Yes / Yes / Yes / No
Inputs/Outputs	
Audio Inputs	6
Digital in: USB-B / optical / coaxial / USB-A	No / No / No / No
Phono Input: MM / MC	Yes / No
Audio Outputs	1
Balanced In / Out	No / No
Pre-out / Main-in	Yes + subwoofer / No
Power Amp Direct In	Yes
Gold-Plated Cinch	Yes
Speaker A / B	Yes
Speaker Terminals	Marantz SPKT-1+
Number of terminals	4
D-Bus	Yes
Headphone Out	Yes
Other	
Linear Drive Power Supply	Yes
Linear volume control	Yes
Schottky diodes	Yes
Input buffer amp (all inputs / CD only)	No / Yes
Solid Heat Sinks	Yes
System block shielding: Copper / metal / none	No / No / Yes
Double Layer Bottom Plate	Triple
Low Noise OLED display	Yes
Source Direct	Yes
Power Amp direct	Yes

Streaming Services			
Power Output (8 / 4 Ω RMS)		70W / 100W	
Frequency Response		5 Hz-10 kHz	
Total Harmonic Distortion		0.02 %	
Damping Factor		100	
Input Sensitivity: MM		1.4mV / 47 k Ω	
Signal to Noise Ratio: MM/MC		87 dB / No	
Input Sensitivity: High level		185 mV / 16 k Ω	
Signal to Noise Ratio: High level		116 dB (2V input)	
Input Sensitivity: Power Amp Direct In		1.5V / 15 k Ω	
Signal to Noise Ratio: Power Amp Direct In		125 dB	
Treble Control		$\pm$ 10 dB at 15 kHz	
Bass Control		$\pm$ 10 dB at 50 Hz	
General			
Available colors		Black, Silver-Gold	
Metal Front Panel		Yes	
Power Consumption		220W	
Standby Consumption		0.3W	
Auto Power off		Yes	
Detachable Power Cable		Yes	
Remote Control		RC003PMND	
System Remote Function		Yes	
Maximum Dimensions (W $\times$ D $\times$ H)		442 $\times$ 431 $\times$ 130 mm	
Weight		14.2 kg	
Carton Maximum Dimensions (W $\times$ D $\times$ H)		527 $\times$ 517 $\times$ 255 mm	
Carton Weight (incl. product)		17.5 kg	
UPC			
USA	Black	MODEL50/U1B	747192141110
USA	Silver-Gold	MODEL50/U1SG	747192141127

Design and specifications are subject to change by Marantz without notice.

www.marantz.com

